

Products > Motor oils for cars and transporters > Synthetic engine oils > CHEMPIOIL Ultra XJP 5W-20



## 9726 CHEMPIOIL ULTRA XJP 5W-20

Innovative energy-saving premium bi-synthetic engine oil (PAO + esters) for modern gasoline engines. Designed to meet the requirements of American, Japanese and Korean automakers.

Product properties:

- Exceptional fuel economy due to reduced high-temperature viscosity HTHS and optimal anti-friction properties;

- Highly effective additive package and low-viscosity synthetic base provide confident cold start in the most severe conditions, thereby significantly reducing engine starting wear;

- Due to its excellent washing and dispersing properties and the highest thermal oxidative stability, it effectively fights against all types of deposits and keeps engine parts clean throughout the entire interval between replacements. Helps to remove previously formed deposits;

- The ester oil components provide excellent anti-wear properties due to the exceptional strength of the oil film, which, combined with excellent pumpability, significantly increases engine life even in "start-stop" driving modes;

- Compatible with the latest exhaust gas aftertreatment systems.

- A special low-viscosity base optimizes the operation of engines with direct injection systems, with turbocharging, as well as with various mechanisms for changing the valve timing (VTEC, i-VTEC, VVT-i, VVTL-i, CVVT, VVL, MIVEC, AVCS (AVLS), CVTCS and others.)

- It is used in engines with extended oil change intervals (Long Life) and conventional.

Designed for multi-valve gasoline engines of cars, light SUVs, vans and light trucks, as well as SUV cars and light-duty vans, where the performance level API SP (RC) / ILSAC GF-6A of this viscosity class is required.

Recommended for cars: Ford, Chrysler, GM Honda, Acura, Mazda, Mitsubishi, Hyundai, Kia, Isuzu, Suzuki, Toyota, Nissan, Subaru.

The oil is not suitable for use in heavy trucks and similar vehicles!

## **Corresponds with requirements / specifications / products:**

Specifications:

## SAE 5W-20 API SP (RC) ILSAC GF-6A **Recommendation:** GM dexos1 Gen2 CHRYSLER MS-6395 FORD WSS-M2C925-B

FORD WSS-M2C930-A FORD WSS-M2C930-B MAZDA SUZUKI FORD WSS-M2C925-A GM 6094M HONDA HTO-06 CHRYSLER MS-13340 JAGUAR STJLR.51.5122 LAND ROVER STJLR.51.5122 FIAT 9.55535-CR1 FORD WSS-M2C945-B1 FORD WSS-M2C948-B HYUNDAI KIA TOYOTA MITSUBISHI

## Volume / weight

5L (CH9726-5) 1L (CH9726-1) 4L (CH9726-4) 20L (CH9726-20) 60L (CH9726-60) 208L (CH9726-DR)