

Products > Oils for agricultural and construction machinery > Super tractor oil universal > CHEMPIOIL Multifarm STOU 10W-40



## 2502 CHEMPIOIL MULTIFARM STOU 10W-40

A truly universal all-weather semi-synthetic motor-transmission (HC-synthes) engine oil for modern diesel engines of agricultural machinery with and without turbocharger operating in difficult conditions, as well as for mechanical transmissions, wet-type braking systems and even tractor hydraulic systems. Designed specifically to solve the specific problems of agricultural machinery, to protect the equipment and get the most out of it, regardless of the conditions of its operation. Belongs to the class STOU (abbr. From Super Tractor Oil Universal).

A feature of the use of agricultural machinery is the high dependence of the operating mode on weather conditions, the possibility of round-the-clock operation, remoteness from service centers, a large assortment of additional attachments and, as a rule, low technical training of personnel. The use of Multifarm STOU 10W-40 eliminates equipment breakdowns associated with confusion in the use of oil, when, due to the storage in the open air, the marking on containers under the influence of weather factors becomes unreadable. The use of oil makes accounting and storage easier. In the field, it is enough to take one canister and in any situation, solve the issue of adding oil to any unit.

## Product properties:

- Innovative additives in combination with a semi-synthetic base of the highest quality with a high viscosity index provide excellent anti-friction, anti-wear and extreme pressure properties, which significantly prolongs the life of the equipment in all, even the most extreme, operating modes in a wide range of ambient temperatures and provides fuel economy; - Synthetic components in combination with natural antioxidants give the oil increased thermal oxidative stability, which, combined with excellent detergent-dispersant properties (TBN> 10), effectively reduces carbon and varnish formation, prevents the formation of deposits of all kinds and maintains engine parts and transmission in excellent cleanliness throughout the interval between replacements;

- A unique HC-containing formulation provides oil resistance to oxidation and aging, and due to reduced volatility and high flash point, reduces oil consumption "for waste";

- Due to the HC-containing base, the optimal viscosity has excellent low-temperature properties, including a low pour point, which provides excellent oil pumpability and cranking of engine and transmission components at low temperatures, easy "cold start" (up to -30°C) and lower starting wear and tear;

- Effectively protects engine parts and transmissions from all types of corrosion, and seals against corrosion by acids;

- Has reduced foaming;

- A special additive package is developed taking into account the difficult Russian operating conditions and low fuel quality. Designed for all types of highly loaded diesel engines of agricultural machinery, where the level of operational properties of CG-4 or lower is required, and for highly loaded mechanical transmissions of this equipment where a level of operational properties of GL-4 is required.

Applicable for hydraulic systems, hydrostatic and mechanical transmissions, wet brakes and multi-plate clutches, power take-off shaft and power steering for all types of tractor equipment.

It can be used in gasoline engines where API SF or lower performance is required.

## **Corresponds with requirements / specifications / products:**

Specifications: SAE 10W-40 API CG-4/CF-4/CF/CE/CD/SF API GL-4 **Recommendation:** ACEA E3 FORD ESN-M2C134-D FORD WSS-M2C159-B FORD WSS-M2C159-C **JOHN DEERE J27** JOHN DEERE J20C MASSEY FERGUSON M 1135 MASSEY FERGUSON M 1139 MASSEY FERGUSON M 1144 MASSEY FERGUSON M 1145 DIN 51524-3 HVLP VOLVO WB 101 Others VOLVO WB 101, suitable for wet brakes ALLISON C4 CASE I H MS 1204 CASE I H MS 1206 CASE I H MS 1207 CASE I H MS 1209 CASE NEW HOLLAND MAT 3525 CASE NEW HOLLAND MAT 3526 CATERPILLAR TO-2 FORD ESN-M2C86-B FORD ESN-M2C86-C FORD NEW HOLLAND 82009201 FORD NEW HOLLAND 82009202 FORD NEW HOLLAND 82009203 JOHN DEERE J20D MASSEY FERGUSON M 1143 MB 227.1 MB 228.1 ZF 06A ZF 06C

ZF 07B ZF 06B (INC. 06R) EATON M-2950-S/I-286-S SPERRY VICKERS M-2950-S/I-286-S SAUER SUNDSTRAND DANFOSS Hydro Static Trans Fluid FENDT KDM 41.2011

## Volume / weight

208L (CH2502-DR) 20L (CH2502-20)