# CHEMPOIL

Products > Motor oils for trucks and buses > UHPD engine oils > CHEMPIOIL CH-23 Truck UHPD 5W-30



## 9123 CHEMPIOIL CH-23 TRUCK UHPD 5W-30

Innovative energy-saving synthetic (contains PAO) low-viscosity engine oil developed for the latest generation of turbocharged diesel engines operating under severe conditions, using ultra-low sulphur fuel (15 ppm or less) and equipped with exhaust gas aftertreatment systems: SCR, EGR and DPF. Provides engine protection in accordance with EPA 2010 and GHG 17. Developed to meet the requirements of Volvo and Daimler.

#### Product properties:

- Improves fuel economy (up to 0.5 % compared to 10W-30 oils and up to 1.3 % compared to 15W-40 oils) and has extended change interval due to increased shear stability and very low volatility;
- The unique low-viscosity synthetic base of the highest quality, combined with a unique additive package and viscosity modifiers, provides an increased viscosity index and unrivalled anti-friction, anti-wear and anti-scuffing properties, which significantly extends the service life of machinery in all, even the most extreme, operating modes in a wide enough range of ambient temperatures and provides unrivalled shear stability;
- The synthetic base, special surfactants and TBN-busters give the oil increased thermal oxidation stability, excellent detergent-dispersing properties and low ash content, which effectively reduces carbon and lacquer formation, prevents the formation of deposits of all kinds and keeps engine separate parts, especially the cylinder-piston group, perfectly clean throughout the entire interval between changes;
- Due to a low viscosity PAO-containing base it has excellent low-temperature properties, including a low pour point, which provides excellent oil pumpability and engine components turnability at low temperatures, easy "cold start" (down to -45 °C)

and reduced starting wear;

- Effectively protects engine separate parts from all types of corrosion;
- Effectively prevents the increase of shear force during operation caused by viscosity increase due to soot dispersion;
- Maintains the efficiency of exhaust gas aftertreatment systems over a long period of time, extends their service life and reduces losses caused by clogging of diesel particulate filters (DPF).

Designed for engines of 2021 and later versions installed in on-road (long-haul tractors, buses, etc.), off-road (construction, mining, agricultural) and special-purpose vehicles of European, American and Asian manufacturers meeting Euro VI and EPA 10 requirements where API FA-4 performance level is required. Oils of this category are not interchangeable and backwards compatible with oils of CK-4 category and its predecessors. Can be used in light diesel engines and in diesel engines without diesel particulate filters (DPF).

## **Corresponds with requirements / specifications / products:**

#### **Specifications:**

**SAE 5W-30** 

API CK-4

JASO DH-2

JASO DH-1

IASO DL-0

MAN M 3777

MAN M 3775

ACEA E4-22

**ACEA E7-22** 

ACEA E11-22

DAIMLER DTFR 15C120

MB 228.51

MB 228.31

MAN M 3677

MAN M 3477

MAN M 3271-1

SCANIA LDF-4

MTU Category 3.1 and Category 2.1

VOLVO VDS-4.5

MACK EOS-4.5

RENAULT RLD-4

CATERPILLAR ECF-3

**CUMMINS CES 20086** 

**CUMMINS CES 20081** 

DETROIT DIESEL DFS 93K222

**DETROIT DIESEL DFS 93K218** 

DAF Extender Drain

ACEA E8-22

## **Volume / weight**

208L

20L

1000L