CHEMPOIL

Products > Gear oils and transmission fluids > Automatic transmission fluids > CHEMPIOIL Fluid DCT



8905 CHEMPIOIL FLUID DCT

A special synthetic gear oil (containing PAO) for DCT – dual clutch transmission/DSG – Direct Shift Gearbox or "robots". It is not recommended for gearboxes with a "dry" clutch. It ensures a flawless operation of a gearbox, guarantees minimal wear, a lasting service life and fuel economy.

Product properties:

- The unique low-viscosity PAO base of the highest quality in combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45 °C and less) temperatures in winter and ensures a stable oil film under extreme loads and high temperatures in summer;
- The high-technology combination of additives ensures good antifriction properties for gear couplings and superior friction properties for friction elements thus ensuring a significant fuel economy, a continuous and smooth transmission shift and the increase in the service life of all transmission elements (friction clutches, hydraulic servo drives, synchronizers, gear pairs);
- It has an increased thermal-oxidative stability and an excellent resistance to the high-temperature thermal degradation that allow increasing the time between oil changes and reducing equipment maintenance costs;
- It protects metal parts from ferrous and non-ferrous alloys from corrosion when both in and not in operation;
- It effectively resists aeration and foam formation;
- It provides an excellent compatibility with sealing materials, prevents them from swelling, hardening and shrinking thus reducing the costs for spare parts and preventing leakages;
- It reduces noise.

It is recommended for transmissions of VW/AUDI, BMW, FORD, PEUGEOT/CITROEN, VOLVO, CHRYSLER, DODGE, MITSUBISHI passenger cars and ZF gearboxes, as well as transmissions of commercial vehicles that require a special oil with indicated

specifications.

Colour: yellow-brown.

Comply with the manufacturer's instructions provided in the user's manual!

Recommendation:

VOLKSWAGEN G 052 182

VOLKSWAGEN G 052 529

BMW 83 22 2 148 578

BMW 83 22 2 148 579

BMW 83 22 0 440 214

BMW 83 22 2 147 477

FORD WSS-M2C936-A

MB 236.21

MB 001 989 85 03

MITSUBISHI MZ320065

PORSCHE 999.917.080.00

PSA 9734.S2

VOLVO 1161838

VOLVO 1161839

VOLKSWAGEN 6-speed

BMW Drivelogic 7-speed (Getrag)

BMW DCTF-1/ DCTF-1+

BMW 6-speed DCT

BMW MTF-LT-5

RENAULT EDC 6-speed (Getrag)

RENAULT EDC-7

RENAULT Talisman R7D

CHRYSLER 68044345 EA&GA

CHRYSLER Powershift 6-speed (Getrag)

FERRARI 7-speed (Getrag)

MITSUBISHI TC-SST 6-speed (GFT)

NISSAN WSS-M2C936-A

PEUGEOT DCS 6-speed (GFT)

FERRARI TF DCT-3

PENTOSIN FFL-8

Others SHELL TF DCT-F3

CASTROL u0412u041eu0422 341

CASTROL u0412u041eu0422 450

BORG WARNER null

BUGATTI_VEYRON null

Volume / weight

1L (CH8905-1)