CHEMPOIL

Products > Motor oils for cars and transporters > Synthetic engine oils > CHEMPIOIL Ultra FR 5W-30



9731 CHEMPIOIL ULTRA FR 5W-30

Innovative energy-saving ester-containing fully synthetic premium engine oil specially developed for modern diesel engines and a number of petrol engines in FORD and VOLVO vehicles, considering the requirements for heavy-duty operation and extended engine oil change intervals. The oil can be used in petrol and diesel engines of European and Asian car manufacturers requiring API SN and ACEA A5/B5 oils.

Product properties:

- Ester components provide excellent anti-wear and anti-friction properties due to the exceptional durability of the oil film, which, combined with excellent pumpability, significantly increases engine life even in "start-stop" mode;
- Significantly saves fuel due to the reduced high-temperature viscosity (HTHS) and excellent anti-friction properties;
- Effectively protects the timing belt from wear, offers an increased total base number (TBN) and excellent compatibility with sealing materials, following additional requirements of FORD;
- Provides easy, low-temperature engine starting due to its excellent pumpability and particularly turnability, which significantly reduces engine starting wear;
- Effectively protects the timing belt from wear, offers an increased total base number (TBN) and excellent compatibility with sealing materials, following additional requirements of FORD;
- A synthetic base guarantees low volatility and reduced operating consumption;
- Excellent washing and dispersing properties, together with the highest thermal-oxidative stability, effectively prevent all types of deposits and keep engine separate parts clean throughout the oil change interval;

- Due to its high thermal-oxidative stability, it resists ageing effectively, thus extending the oil change interval;
- Suits bio diesel engines.

Designed for diesel engines of passenger vehicles by FORD, VOLVO and GM, where SAE 5W-30 oil is recommended, which complies with the ACEA A5/B5 standard and meets FORD WSS-M2C913-D specification, as well as for petrol and diesel engines of these brands where previous specifications 913-C, 913-B and 913-A oils are recommended. The oil is not suitable for use in heavy trucks and similar vehicles!

Specifications:

SAE 5W-30

Recommendation:

API SP
ACEA A5/B5
FORD WSS-M2C913-D
FORD WSS-M2C913-C
FORD WSS-M2C913-B
FORD WSS-M2C913-A
VOLVO VCC 95200377 (Service Fill)
MB 229.6
FIAT 9.55535-G1
JAGUAR STJLR.03.5003
LAND ROVER STJLR.03.5003

Volume / weight

5L (CH9731-5) 1L (CH9731-1) 60L (CH9731-60) 208L (CH9731-208)