CHEMPOIL

Products > Motor oils for cars and transporters > Synthetic engine oils > CHEMPIOIL Ultra PD 5W-40



9719 CHEMPIOIL ULTRA PD 5W-40

Innovative universal energy-saving ester-containing fully synthetic premium motor oil for modern diesel engines (including those with direct injection) and gasoline engines with and without turbocharging, including those equipped with pump nozzles (Pumpe-Duse). Designed based on VW and DAIMLER requirements.

Product properties:

- Due to the contained ester components it has excellent anti-seize, anti-wear and anti-friction properties;
- Due to its excellent washing and dispersing properties and the highest thermal oxidative stability, it effectively fights against all types of deposits and keeps engine parts clean throughout the entire interval between replacements;
- Saves fuel due to reduced high-temperature viscosity HTHS optimal antifriction properties;
- The ester components in combination with a synthetic base guarantee an easy low-temperature engine starting due to exceptional indicators of cranking and pumpability, which significantly reduces engine starting wear;
- Ester technology and a synthetic base with an expanded range of viscous-temperature properties ensures efficient engine operation in all operating modes: during cold start, in urban mode, in highway mode, as well as under increased load (when driving on impassable roads, uphill, on the move with trailer, maximum load) and at high ambient temperatures;
- Due to the high thermo-oxidative stability, it effectively resists aging;
- Compatible with all exhaust gas aftertreatment systems, DPF, TWC, EGR and SCR through the use of Mid SAPS technology;
- It is applied in engines with the extended interval of replacement of oil (Long Life) and ordinary;
- Suitable for engines using liquefied natural gas (LNG) and (LPG) petroleum gas.

Designed for gasoline and diesel engines of the EURO IV and EURO V standard of a wide fleet of cars (cars, light SUVs, minibuses and light trucks) of European and other manufacturers).

Recommended for use in engines of Daimler, BMW, VW cars, which impose additional requirements for engine oils (according to the above specifications).

The oil is not suitable for use in heavy trucks and similar vehicles!

Corresponds with requirements / specifications / products:

Specifications:

SAE 5W-40

API SN

ACEA C3

GM dexos2

MB 229.31

RENAULT RN0700

RENAULT RN0710

VOLKSWAGEN 505 01

FORD WSS-M2C917-A

VOLKSWAGEN 505 00

MB 229.51

PORSCHE A40

Recommendation:

BMW Longlife-04

CHRYSLER MS-11106

FIAT 9.55535-S2

FIAT 9.55535-GH2

ACEA C2

Volume / weight

5L (CH9719-5)

1L (CH9719-1)

4L (CH9719-4)

20L (CH9719-20)

60L (CH9719-60)

208L (CH9719-DR)